TECHNICAL SPECIFICATION

Printing Technology

Print Head	Drop On Demand Piezoelectric Head
No. of print head	Two or Three Heads
Productivity	EPS3200
Express	120sqm/h (v360×1200dpi)
Production	90sqm/h (v360×1800dpi)
Quality	60sqm/h (V360×2400dpi)

Resolution & Software

Resolutions	2400dpi Max.
Software	Standard (Maintop/photoprint); Onyx, Caldera,Neostampa available as optional

Media

Media Width	Maximum 1920mm
Roll diamention & Weight	Max. 210mm, 40KG
Print Width	1880mm in one roll; 2 rolls 914mm together
Feeding&Taking-up System	Industrial Auto-Feeding&taking-up system with tension arm

Inks

Туре	Dye Sublimation
Ink Supply System	1.5L Large Bulk System with automatic supply system
Colors	Standard CMYK; Others Configuration Optional
Ink curing system	Integrated Heating System, Extend infrared heating and cooling system

Dimensions & Weight

Machine(L*W*H)	3270×1230×1840mm
Package(L*W*H)	3710×770×850mm

Operation Requirements

Connectivity	Hi-Speed USB 3.0
Power	Single Phase, 220VAC±10%, 50/60Hz; 2500W(Machine),3000W(Heater)
Environment	Temp. 15~30°C; RH 40~60%;

Warranty

dealer

X Specifications are subject to change without notice

บริษัท ไฮแมททีเรียลเซอร์วิส จำกัด HIGH MATERIAL SERVICES Co.,Ltd.

www.highmaterial.com, xu_numchai@hotmail.com











production 90 sqm/h

LATEST 3HEADS

LARGE-FORMAT PRINTER FOR SUBLIMATION INKS



FASTEST AND EASIEST OF USE!

PROFESSIONAL DIGITAL INKJET TEXTILE PRINTER SUPPLIER

